


CAROLINA TRAILERS & EQUIPMENT



25 Ton Lowboy

40' Overall



Framework

Mainframe:	14" WF @ 26# per foot
Crossmembers:	Pierced Through Frame, 4" WF 13 # per foot on 24" Center
Side Rails:	8" Channel
Flooring:	2" Treated Oak
Ramps:	8" Channel, 5' Fold-Over w/ Spring Assist

Undercarriage

Brakes:	Air w/ ABS and Park
Tires:	(8) 235-75 R 17.5 SBR 18 PR on (8) 17.5 Steel Disc Wheels
Axles:	(2) 22,500#; Oil Bath
Suspension:	9700 Hutch 4-Spring; Equalizing w/Adjustable Torque Arms

Dimensions

Load Deck Length:	22'
Upper Deck:	9' Flat
Slope:	4' with Traction Cleats
DoveTail:	5' Treated Oak
Width x O/A Length:	102" W x 40' L
D-Rings:	(6) per Side Heavy Duty Cupped Type

More Specs

Electrical/Wiring:	DOT Approved; All Sealed Wiring Harness; Mid-Span Turn Signals; Sealed Beam & Recessed & Rubber-Mounted LED Lighting
Jack:	Dual 2-Speed Landing Gear: 160,000# Vertical Cap., 29,000# Side Load
DOT Conspicuity Tape:	Full Length of Trailer
Flag Holders:	(4) Wide Load Flag Holders
Tool Tray:	In Upper Deck
Step:	(1) Driver's Side Step
Finish:	Sandblasted, Primed and Painted Customer Choice of Standard Colors

AVAILABLE OPTIONS FOR THE 25 TON LOWBOY (Partial Listing)

- | | | |
|---|---|----------------------------|
| *Locking Under Body Toolbox(es) | *Winch & Cable | *Additional D-Rings |
| *Tire/Wheel Combinations | *Ratchet Track w/Sliding Winches | *Recessed D-Rings in Floor |
| *Alcoa Aluminum Wheels:
(Inside Polished w/Nut Covers) | *Spare Carrier | *Air Ride Suspension |
| *Stainless Steel Simulators | *Spare Tire & Wheel | *Swing-Out Outriggers |
| *Ramp Styles & Dimensions | *Bucket Plate | *Wide-Track Axles |
| *Trailer Configurations:
(Arrangements, Width, Length) | *Strobe Lights | *Upgrade to 30-Ton |
| | *Inside/Outside Guides
(for Track Equipment) | *Front Headboard |
| | | *Side-Rail Cut-Outs |