

CAROLINA TRAILERS & EQUIPMENT



Trailer: 30 Ton Tri-Axle Tilt

Standard Specifications

*All Dimensions, Such As Stationary Floor Length, Tilt Floor Length, Width, etc., Are Variable.
Dimensions May be Built To Customer Specifications.*

Framework

Mainframe:	10" @ 30# per ft WF
Tilt Frame:	10" @ 30# per ft Channel
Crossmembers:	3 x 3 x 1/4" Tubular
Dovetail:	18" Traction Cleat
Deck Height:	35" +/- (Unloaded)
Flooring	2" Oak w/ Treadplate over Axles

Undercarriage

Axles:	(3) 25K, Wide Track w/ABS & Park
Brakes:	Air
Tires & Wheels:	(12) 235 18-Ply on 17.5 Steel Disc
D-Rings	Min. (6) per side, H.D. Cupped Type
Jack	25,000# Drop Leg, 2-Speed

Dimensions

Length:	24' Tilt; 5' Stationary
Width:	102"
Hitch:	Adjustable 4 Bolt Pintle 100K#

Misc.

Electrical: All Sealed Wiring Harness
Lighting: DOT Approved, All Rubber-Mounted, Recessed w/LED Lighting on Rear
Driver's Side Step
Tool Tray w/ Lid
Paint: Sandblasted, Primed and Painted Customer Choice of Standard Colors