

CAROLINA TRAILERS & EQUIPMENT



Trailer: 50 Ton Lowboy

*Available in 25-50 Ton Models with Optional Dimensions
(length, width, neck design)*

Standard Specifications

Framework

Mainframe:	18" WF Beam @ 50# per foot
Crossmembers:	6" WF @ 12# per foot on 24" Centers
Flooring:	2" Nominal Oak
Ramps:	5' Fold-Over, Spring Assist, Bar-Up
Coupler:	Kingpin
DoveTail:	5' Wood or Traction Cleat

Undercarriage

Axles:	(3) 25,000# Dana Wide Track w/Auto Slack Adjusters
Jack:	2-Spd Landing Gear; Dual Jacks; 50,000 lb. Capacity
Brakes:	ABS & Park Brake
Tires:	(12) 255/70 R 22.5 Low Profile
Wheels:	10-Hole Budd

Dimensions

Load Deck Length:	28' Flat
Upper Deck:	10' Standard Wood
Slope:	5' Wood or Traction Cleat
Width:	102"
Side Rails:	12" Channel @ 20# per foot
D-Rings:	Heavy Duty Cupped Type

More Specs

Electrical:	All Sealed Wiring Harness; All Rubber-Mounted Lights
Finish:	Sandblasted, Primed & Painted Throughout
Toolbox:	on Upper Deck, additional Tool Box, Driver's Side